

BIPRO

108-cell

SYSTEM & PRODUCT CERTIFICATES





PERFORMANCE WARRANTY











12BB Half-cut Cell Technology



Industry Leading High Yield



Excellent Anti-PID Performance



Wider Application



IP68 Junction Box



				ΓFR	

Testing Condition	STC	имот	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)				 		 		 		
Operating Voltage (Vmpp/V)				1		 		! !		
Operating Current (Impp/A)				1		 		1 1		
Open-Circuit Voltage (Voc/V)				1		 		1		
Short-Circuit Current (Isc/A)				1		 		1		
Module Efficiency (%)	/	/								

STC: Irradiance 1000W/m², Spectra at AM1.5, Module Temperature 25 °C. Power output tolerance: 0~+5W, Test uncertainty for Pmax: ±3% NMOT: Irradiance 800W/m², Spectra at AM1.5, Ambient Temperature 20 °C, Wind speed 1m/s

REAR SIDE POWER GAIN(REFERENCE TO 545W FRONT)

Pmax gain				
Pmax/W	/	/		
Vmpp/V				
Impp/A Voc/V				
Voc/V				
Isc/A	/			

MECHANICAL CHARACTERISTICS

	_
Cell Type	
No. of Cells	
Module Dimensions	
Weight	
Front Glass	
Back Glass	
Frame	
Junction Box	
Output Cables	
Connectors	

APPLICATION CONDITIONS

Maximun System Voltage	
Operating Temperature	
Maximun Series Fuse	
Safety Protection Class	П
Mechanical Load	
Refer. Bifaciality Factor	


TEMPERATURE CHARACTERISTICS


Temperature Coefficient of Pmax	
Temperature Coefficient of Voc	
emperature Coefficient of Isc	
Nominal Module Operating Temperature(NMOT)	

PACKING CONFIGURATION

Pieces Per Pallet	
Pieces Per Container(40'HQ)	

I-V CURVE





TECHNICAL DRAWINGS

