

TP6L60M(H) **120-cell**

360 - 380W 9BB Half-cut Mono Perc

SYSTEM & PRODUCT CERTIFICATES



- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems





PERFORMANCE WARRANTY





Linear Performance Warranty



KEY FEATURES



9BB Half-cut Cell Technology

New circuit design, lower internal current, lower Rs loss Ga dopped wafer, attenuation < 2% [1st year] / 0.55% [Linear]



Excellent Anti-PID Performance

2 times of industry standard Anti-PID test



Wider Application

No water-permeability and high wear-resistance, can be widely used in high-humid, windy and dusty area



IP68 Junction Box

High waterproof level

ELECTRICAL CHARACTERISTICS

			1	
1			1	1
1				
1	1	1		1
1			1	
1			1	1
19.70	20.00	20.30	20.60	20.90

. C. :

MECHANICAL CHARACTERISTICS

Monocrystalline Silicon (9Busbar)
120pcs in series (6*20)
1755*1038*30mm (69.09*40.87*1.18 inches)
19.5kg (42.99lbs)
Anodized Aluminium Alloy
IP68, 3 Bypass Diodes
4mm²(IEC),12AWG(UL) 300mm in Length or Customized Length
T01/LJQ-3-CSY/MC4/MC4-EV02

I-V CURVE

TECHNICAL DRAWINGS

TEMPERATURE CHARACTERISTICS

1

PACKING CONF

