



TALESUN

# BIPRO

TM3G48M **96-cell**

435 - 455 W

16BB N



## 产品特性

## 体系及产品认证

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015
- ISO 14001: 2015
- ISO 45001: 2018



## 质量保证

保证功率

 [www.talesun.com](http://www.talesun.com)

 [marketing.hq@talesun.com](mailto:marketing.hq@talesun.com)

|  | STC   | NMOT | STC   | NMOT | STC   | NMOT | STC   | NMOT | STC   | NMOT |
|--|-------|------|-------|------|-------|------|-------|------|-------|------|
|  |       |      |       |      |       |      |       |      |       |      |
|  |       |      |       |      |       |      |       |      |       |      |
|  |       |      |       |      |       |      |       |      |       |      |
|  |       |      |       |      |       |      |       |      |       |      |
|  | 21.80 |      | 22.00 |      | 22.30 |      | 22.50 |      | 22.80 |      |

|  | 5%    | 10%   | 15%   | 20%   | 25%   |
|--|-------|-------|-------|-------|-------|
|  | 467   | 490   | 512   | 534   | 556   |
|  | 29.79 | 29.79 | 29.79 | 29.79 | 29.79 |
|  | 15.69 | 16.43 | 17.18 | 17.93 | 18.68 |
|  | 35.42 | 35.42 | 35.42 | 35.42 | 35.42 |
|  | 16.62 | 17.41 | 18.20 | 19.00 | 19.79 |

|  |  |      |
|--|--|------|
|  | N  | 16BB |
|  | 96 (6*16)  |      |
|  | 1762*1134*30mm (69.37*44.65*1.18 )                       |      |
|  | 24.7kg (54.45lbs)  |      |
|  |  |      |
|  |  |      |
|  | IP68, 3  |      |
|  | 4mm <sup>2</sup> (IEC), 12AWG (UL)<br>350mm(+), 250mm(-) |      |
|  | T01/LJQ-3-CSY/MC4/MC4-EVO216                             | D    |

©